




LTR	REV.	DESCRIPTION	DATE

MD 6P FEMALE



THUMB SCREW #4-40 UNC*2PCS
(T/N: TAD-0006)

DB9P FEMALE
PLASTIC:BLUE



P1	P2
2	2
3	5
6	7
SHELL	SHELL

NOTES

1.HOOK UP WIRE: 28AWG(7/0.127)TINNED COPPER*3C SR-PVC

2.CONNECTORS:

P1:MD6P FEMALE GOLD FLASH CONTACT,
NICKEL PLATED SHELL

P2:DB9P FEMALE GOLD FLASH CONTACT,
NICKEL PLATED SHELL

3.HOOD:MOLDED TYPE,PVC 45P,COLOR:BEIGE(NK-A03)

4.TEST REQUEST:

<1>.100% OPEN SHORT & MIS WIRE TEST

<2>.CONTACT RESISTANCE 3Ω MAX

<3>.INSULATION RESISTANCE 20MΩ MIN

5.PACKING:SEE P-0039 REV.C PACKING DRAWING
EAN CODE:4016032118824

Tolerance	Inch	M/M
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05

NEOSTAR TECHNOLOGY CO., LTD.

Draw KIKI 04/17	Title DB 9F/MD 6F ADAPTOR		
Check	App'd	Customer	E-SSM
Engr	Scale	NONE	Units m/m
	Dwg No. 160-0702	REV:A	Sheet 1/1